

Jonathan,

I didn't get many hits (records) when I searched ~~on~~ copper iodate. I tried broadening the search with cupric iodate etc. but didn't get any additional hits. I also searched a wide variety of files: material science files - Copper, and metals (Metadex); fuel cell related - Energy, general science - Conferences (Confsci) Scisearch Electrical .... you get the idea.

John

703-308-4139

=> file hca

FILE 'HCA' ENTERED AT 11:23:12 ON 03 DEC 2003  
USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.  
PLEASE SEE "HELP USAGETERMS" FOR DETAILS.  
COPYRIGHT (C) 2003 AMERICAN CHEMICAL SOCIETY (ACS)

Copyright of the articles to which records in this database refer is held by the publishers listed in the PUBLISHER (PB) field (available for records published or updated in Chemical Abstracts after December 26, 1996), unless otherwise indicated in the original publications. The CA Lexicon is the copyrighted intellectual property of the American Chemical Society and is provided to assist you in searching databases on STN. Any dissemination, distribution, copying, or storing of this information, without the prior written consent of CAS, is strictly prohibited.

=> d his nofile

(FILE 'HOME' ENTERED AT 10:44:33 ON 03 DEC 2003)

FILE 'HCA' ENTERED AT 10:45:01 ON 03 DEC 2003  
E US20030049530/PN

L1 1 SEA ABB=ON PLU=ON US2003049530/PN  
D SCAN  
SEL L1 RN

FILE 'REGISTRY' ENTERED AT 10:45:20 ON 03 DEC 2003

L2 11 SEA ABB=ON PLU=ON (1310-58-3/BI OR 1313-13-9/BI OR 1314-13-2/  
BI OR 13454-89-2/BI OR 310881-75-5/BI OR 39464-64-7/BI OR  
500731-88-4/BI OR 7440-44-0/BI OR 7440-66-6/BI OR 7704-34-9/BI  
OR 7782-42-5/BI)  
D SCAN

L3 1 SEA ABB=ON PLU=ON L2 AND IODIC

FILE 'HCA' ENTERED AT 10:46:20 ON 03 DEC 2003

L4 73 SEA ABB=ON PLU=ON L3  
L5 242477 SEA ABB=ON PLU=ON FUELCELL? OR BATTERY? OR BATTERIES? OR  
(FUEL? OR ELECTROCHEM? OR ELECTRO(W)CHEM? OR GALVAN? OR  
ELECTROLY? OR SECONDAR? OR PRIMAR?) (2A)CELL? OR FC OR SOFC OR  
DFC OR PEMFC  
L6 700600 SEA ABB=ON PLU=ON ELECTROD## OR ANOD### OR CATHOD###  
D L1 ABS  
L7 73 SEA ABB=ON PLU=ON (CU OR COPPER#) (A) IODATE?  
L8 95 SEA ABB=ON PLU=ON L4 OR L7  
L9 4 SEA ABB=ON PLU=ON L8 AND L5  
L10 5 SEA ABB=ON PLU=ON L8 AND L6  
L11 3 SEA ABB=ON PLU=ON L9 AND L10  
D SCAN  
L12 6 SEA ABB=ON PLU=ON L9 OR L10 OR L11  
L13 3 SEA ABB=ON PLU=ON L12 NOT L11

FILE 'WPIX, JAPIO' ENTERED AT 11:01:54 ON 03 DEC 2003

L14 7 SEA ABB=ON PLU=ON L7  
L15 353275 SEA ABB=ON PLU=ON L5  
L16 1043862 SEA ABB=ON PLU=ON L6  
L17 2 SEA ABB=ON PLU=ON L14 AND L16  
L18 1 SEA ABB=ON PLU=ON L14 AND L15  
L19 2 SEA ABB=ON PLU=ON L17 OR L18  
D SCAN

FILE 'COMPENDEX, INSPEC' ENTERED AT 11:05:02 ON 03 DEC 2003

L20 6 SEA ABB=ON PLU=ON L7  
L21 0 SEA ABB=ON PLU=ON L20 AND L6  
L22 0 SEA ABB=ON PLU=ON L20 AND L5

FILE 'INSPHYS, JICST-EPLUS, METADEX, SCISEARCH, SOLIDSTATE' ENTERED AT  
11:08:24 ON 03 DEC 2003

L23 3 SEA ABB=ON PLU=ON L7  
L24 0 SEA ABB=ON PLU=ON L23 AND L6  
L25 0 SEA ABB=ON PLU=ON L23 AND L5  
D SCAN L23

FILE 'RUSSCI, CONFSCI, ENERGY' ENTERED AT 11:11:36 ON 03 DEC 2003

L26 3 SEA ABB=ON PLU=ON L7  
L27 106281 SEA ABB=ON PLU=ON L6  
L28 0 SEA ABB=ON PLU=ON L26 AND L27

FILE 'COPPERLIT, CORROSION, NTIS' ENTERED AT 11:16:15 ON 03 DEC 2003

L29 5 SEA ABB=ON PLU=ON L7  
L30 53993 SEA ABB=ON PLU=ON L6  
L31 2 SEA ABB=ON PLU=ON L29 AND L30  
D SCAN

FILE 'REGISTRY' ENTERED AT 11:17:28 ON 03 DEC 2003

D L3 FIDE

FILE 'WPIX' ENTERED AT 11:18:02 ON 03 DEC 2003

L32 18 SEA ABB=ON PLU=ON (COPPER# OR CUPRIC# OR CUPROUS# OR  
CUPRITE#) (2A) (?IODATE?)  
L33 2 SEA ABB=ON PLU=ON L16 AND L32  
D SCAN

FILE 'JAPIO' ENTERED AT 11:22:09 ON 03 DEC 2003

L34 2 SEA ABB=ON PLU=ON (COPPER# OR CUPRIC# OR CUPROUS# OR  
CUPRITE#) (2A) (?IODATE?)  
L35 0 SEA ABB=ON PLU=ON L16 AND L34

=&gt; d L11 1-3 ibib abs hitind hitrn

L11 ANSWER 1 OF 3 HCA COPYRIGHT 2003 ACS on STN  
ACCESSION NUMBER: 138:224220 HCA  
TITLE: Alkaline **battery** with **copper**  
**iodate cathode**

(Author's Record)

INVENTOR(S): Wang, Francis P.; Xue, J. Simon; Anglin, David;

Rozelle, James; Drennan, Joseph; Wang, Enoch I.

PATENT ASSIGNEE(S): USA

SOURCE: U.S. Pat. Appl. Publ., 11 pp.

CODEN: USXXCO

DOCUMENT TYPE: Patent

LANGUAGE: English

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
US 2003049530	A1	20030313	US 2001-941526	20010829
PRIORITY APPLN. INFO.:			US 2001-941526	20010829
AB An alkaline cell has an <b>anode</b> comprising zinc, an alkaline electrolyte solution, a separator, and a <b>cathode</b> comprising <b>copper iodate</b> . The <b>cathode</b> preferably also includes a graphitic carbon to improve elec. conductivity The graphitic carbon can comprise natural or synthetic graphites including expanded graphites and graphitic carbon fibers. Preferably, the graphitic carbon comprises graphitic carbon nanofibers. The carbon nanofibers desirably have a mean average diameter less than 500 nm. The <b>cathode</b> can also include sulfur in admixt. with the <b>copper iodate</b> to improve cell performance.				
IC	ICM H01M004-48			
	ICS H01M004-62; H01M004-58			
NCL	429220000; 429232000			
CC	52-2 (Electrochemical, Radiational, and Thermal Energy Technology)			
ST	<b>battery copper iodate cathode</b>			
IT	<b>Battery cathodes</b>			
	Primary <b>batteries</b>			
	(alkaline <b>battery</b> with <b>copper iodate cathode</b> )			
IT	Carbon fibers, uses			
	RL: DEV (Device component use); USES (Uses)			
	(nanofibers; alkaline <b>battery</b> with <b>copper iodate cathode</b> )			
IT	Zinc alloy, base			
	RL: DEV (Device component use); USES (Uses)			
	(alkaline <b>battery</b> with <b>copper iodate cathode</b> )			
IT	1310-58-3, Potassium hydroxide (K(OH)), uses 1313-13-9, Manganese			

dioxide, uses 7440-66-6, Zinc, uses 13454-89-2, Copper  
**iodate**  
 RL: DEV (Device component use); USES (Uses)  
 (alkaline **battery** with **copper iodate**  
**cathode**)  
 IT 1314-13-2, Zinc oxide (ZnO), uses 7704-34-9, Sulfur, uses 39464-64-7,  
 Rm-510 310881-75-5, Waterlock a-221  
 RL: MOA (Modifier or additive use); USES (Uses)  
 (alkaline **battery** with **copper iodate**  
**cathode**)  
 IT 7782-42-5, Graphite, uses  
 RL: DEV (Device component use); USES (Uses)  
 (expanded; alkaline **battery** with **copper iodate**  
**cathode**)  
 IT 500731-88-4, Carbopol C 940  
 RL: MOA (Modifier or additive use); USES (Uses)  
 (gelling agent; alkaline **battery** with **copper**  
**iodate cathode**)  
 IT 7440-44-0, Carbon, uses  
 RL: DEV (Device component use); USES (Uses)  
 (graphitic; alkaline **battery** with **copper iodate**  
**cathode**)  
 IT 13454-89-2, Copper iodate  
 RL: DEV (Device component use); USES (Uses)  
 (alkaline **battery** with **copper iodate**  
**cathode**)

L11 ANSWER 2 OF 3 HCA COPYRIGHT 2003 ACS on STN  
 ACCESSION NUMBER: 132:125374 HCA  
 TITLE: Secondary nonaqueous electrolyte **batteries**  
 INVENTOR(S): Okamura, Kazuhiro; Nitta, Yoshiaki  
 PATENT ASSIGNEE(S): Matsushita Electric Industrial Co., Ltd., Japan  
 SOURCE: Jpn. Kokai Tokkyo Koho, 4 pp.  
 CODEN: JKXXAF  
 DOCUMENT TYPE: Patent  
 LANGUAGE: Japanese  
 FAMILY ACC. NUM. COUNT: 1  
 PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
JP 2000048816	A2	20000218	JP 1998-217252	19980731
PRIORITY APPLN. INFO.:			JP 1998-217252	19980731
AB	The <b>batteries</b> have Li intercalating <b>anodes</b> and metal iodate <b>cathodes</b> .			
IC	ICM H01M004-58 ICS H01M004-02; H01M010-40			
CC	52-2 (Electrochemical, Radiational, and Thermal Energy Technology)			
ST	lithium <b>battery</b> metal iodate <b>cathode</b> .			
IT	<b>Battery cathodes</b> (metal iodate <b>cathodes</b> for secondary lithium <b>batteries</b> )			
IT	22446-84-0, Zirconium iodate [Zr(IO <sub>3</sub> ) <sub>4</sub> ] 29515-61-5, Ferric iodate 256459-53-7, Cobalt iodide oxide (CoI <sub>3</sub> O <sub>9</sub> ) 256459-54-8, Cobalt iron iodide oxide (Co <sub>0.01</sub> Fe <sub>0.99</sub> I <sub>3</sub> O <sub>9</sub> ) RL: DEV (Device component use); USES (Uses) (metal iodate <b>cathodes</b> for secondary lithium <b>batteries</b> )			

IT 13454-89-2

RL: DEV (Device component use); USES (Uses)  
( $\alpha$ - and  $\gamma$ -; metal iodate cathodes for secondary  
lithium batteries)

IT 13454-89-2

RL: DEV (Device component use); USES (Uses)  
( $\alpha$ - and  $\gamma$ -; metal iodate cathodes for secondary  
lithium batteries)

L11 ANSWER 3 OF 3 HCA COPYRIGHT 2003 ACS on STN

ACCESSION NUMBER: 124:187877 HCA

TITLE: Electric work and equivalent galvanic potential of  
non-redox coupling in **galvanic cell**

AUTHOR(S): Jianjun, Huang; Wenjie, Zheng; Ningxing, Huang

CORPORATE SOURCE: Editorial Dept. of Journal, Jinan Univ., Canton,  
510632, Peop. Rep. ChinaSOURCE: Huanan Shifan Daxue Xuebao, Ziran Kexueban (1995),  
(1), 97-101

CODEN: HSDZER; ISSN: 1000-5463

PUBLISHER: Huanan Shifan Daxue

DOCUMENT TYPE: Journal

LANGUAGE: Chinese

AB The non-redox reaction produced in **galvanic cells** is  
the reaction of doing elec. work. The maximum elec. work done by the  
non-redox reaction is equal to its standard change in free energy,  
 $\Delta G_{\text{vphi}}$ . It may be described in terms of the equivalent galvanic  
potential,  $\phi_e$ , for the maximum effect of the non-redox reaction. The  
contribution of non-redox reaction to **electrode** potential is  
discussed using **electrode** reactions.

CC 72-2 (Electrochemistry)

Section cross-reference(s): 65

ST elec work equiv galvanic potential; nonredox coupling **galvanic  
cell**; std change free energy nonredox reaction

IT 534-16-7, Silver carbonate 1309-33-7, Ferric hydroxide 1317-37-9,  
Ferrous sulfide 1345-07-9, Bismuth sulfide 7446-14-2, Lead sulfate  
7758-89-6, Cuprous chloride 7779-90-0, Zinc phosphate 7783-40-6,  
Magnesium fluoride 7783-90-6, Silver chloride, properties 7783-96-2,  
Silver iodide 7784-01-2, Silver chromate 7787-64-6, Bismuth iodide  
10049-01-1, Bismuth phosphate 10101-63-0, Lead iodide (PbI<sub>2</sub>)  
10294-40-3, Barium chromate 11113-75-0, Nickel sulfide 12054-48-7,  
Nickel hydroxide (Ni(OH)<sub>2</sub>) 13454-89-2, **Copper  
iodate** (Cu(IO<sub>3</sub>)<sub>2</sub>) 13767-71-0, Cupric iodide  
15385-58-7, Mercurous bromide (Hg<sub>2</sub>Br<sub>2</sub>) 18624-44-7, Ferrous hydroxide  
18820-29-6, Manganous sulfide 18933-05-6, Manganese hydroxide  
19783-14-3, Lead hydroxide 20427-58-1, Zinc hydroxide 20427-59-2,  
Cupric hydroxide 21548-73-2, Silver sulfide (Ag<sub>2</sub>S) 39377-56-5, Lead  
sulfide 51595-71-2, Mercury sulfide (Hg<sub>2</sub>S)

RL: PEP (Physical, engineering or chemical process); PRP (Properties);  
PROC (Process)

(standard change in free energy in precipitation of)

IT 13454-89-2, **Copper iodate** (Cu(IO<sub>3</sub>)<sub>2</sub>)

RL: PEP (Physical, engineering or chemical process); PRP (Properties);  
PROC (Process)

(standard change in free energy in precipitation of)

=&gt; d L13 1-3 ibib abs hitind hitrn

L13 ANSWER 1 OF 3 HCA COPYRIGHT 2003 ACS on STN

ACCESSION NUMBER: 98:24632 HCA

TITLE: Voltammetry of nitrate and iodate ions at copper-cadmium alloy rotating disk **electrodes**

AUTHOR(S): Kvaratskheliya, R. K.; Machavariani, T. Sh.

CORPORATE SOURCE: Inst. Neorg. Khim. Elektrokhim., Tbilisi, USSR

SOURCE: Collection of Czechoslovak Chemical Communications (1982), 47(10), 2615-22

CODEN: CCCCAK; ISSN: 0366-547X

DOCUMENT TYPE: Journal

LANGUAGE: French

AB The difficult-to-reduce anions NO<sub>3</sub><sup>-</sup> and IO<sub>3</sub><sup>-</sup> form well-expressed waves of the processes: NO<sub>3</sub><sup>-</sup> → NO<sub>2</sub><sup>-</sup> and IO<sub>3</sub><sup>-</sup> → I<sup>-</sup> on rotating disk **electrodes** from Cu-Cd alloys in solns. of alkali metal and alkaline earth metal salts. A change in the composition of the alloy significantly affects the values of the half-wave potentials of the anions. The highest reduction rate of the NO<sub>3</sub><sup>-</sup> and IO<sub>3</sub><sup>-</sup> was observed in the case of an **electrode** of Cd 72-Cu 28 alloy, corresponding to the γ-phase compound Cu<sub>5</sub>Cd<sub>8</sub>. A decrease in the hydrophilic nature of the metal from Cd to Cu has no effect on the kinetics of electroredn. of NO<sub>3</sub><sup>-</sup> and IO<sub>3</sub><sup>-</sup>.

CC 72-10 (Electrochemistry)

Section cross-reference(s): 67

ST voltammetry nitrate **iodate copper** cadmium; nitrate voltammetry copper cadmium alloy; iodate voltammetry copper cadmium alloy; copper cadmium alloy disk **electrode**; redn electrochem nitrate iodate alloy; kinetics electroredn nitrate iodate

IT 84058-21-9

RL: PRP (Properties)

(rotating disk **electrodes**, iodate and nitrate reduction kinetics on)

IT 51398-46-0 65449-87-8 69944-09-8

RL: PRP (Properties)

(rotating disk **electrodes**, reduction kinetics of iodate and nitrate on)

L13 ANSWER 2 OF 3 HCA COPYRIGHT 2003 ACS on STN

ACCESSION NUMBER: 69:54869 HCA

TITLE: Effect of an indifferent electrolyte on the activity of ions of weak acids and precipitates

AUTHOR(S): Vervaet, A.

CORPORATE SOURCE: Rijksuniv., Ghent, Belg.

SOURCE: Mededelingen van de Vlaamse Chemische Vereniging (1968), 30(1), 31-4

CODEN: MVLCA2; ISSN: 0369-2787

DOCUMENT TYPE: Journal

LANGUAGE: Dutch

AB The potential ΔE of a **cell** with an **electrolyte** A in contact with indifferent electrolyte Z was derived by using the Debye-Hueckel theory to find the effect of the concentration when A is a (z<sub>1</sub> - z<sub>2</sub>)-valent precipitate or a weak acid. For Z = KNO<sub>3</sub> and A = AgBrO<sub>3</sub>, AcOH, Cu(IO<sub>3</sub>)<sub>2</sub>, and Cd(IO<sub>3</sub>)<sub>2</sub>, the measured values agreed with the theory; for A = Ag<sub>2</sub>SO<sub>4</sub> they disagreed because solubility of Ag<sub>2</sub>SO<sub>4</sub> was too high.

CC 68 (Phase Equilibria, Chemical Equilibria, and Solutions)

IT Electric potential

(of **electrolytic cells**, activity in relation to)

IT 7783-89-3 7790-81-0 10294-26-5 13454-89-2

RL: PRP (Properties)

(activity of, indifferent electrolyte effects on)

IT 13454-89-2

RL: PRP (Properties)

(activity of, indifferent electrolyte effects on)

L13 ANSWER 3 OF 3 HCA COPYRIGHT 2003 ACS on STN

ACCESSION NUMBER: 7:20168 HCA

ORIGINAL REFERENCE NO.: 7:2911e-g

TITLE: Cupric Iodate

AUTHOR(S): Spencer, J. F.

CORPORATE SOURCE: London

SOURCE: Z. physik. Chem. (1913), 83, 290-6

DOCUMENT TYPE: Journal

LANGUAGE: Unavailable

AB The pale blue crystalline precipitate, obtained by adding an excess of KIO3 solution to a

concentrate solution of Cu(NO3)2, has an H2O and an I2 content which agree with the

formula Cu(IO3)2.H2O. The salt is soluble in HNO3. When heated to redness, it breaks up into CuO, I2 and O2. An **electrode** of the third order, Hg, Hg2(IO3)2.Cu(IO3)2, Cu'', was devised, and was used to meas. the concentrate of Cu''. The equation for the use of the **electrode** is  $\epsilon = 0.6060 + 0.0297 \log Cu''$  at 25°. When used to meas. the concentrate of IO3',  $\epsilon = 0.4027 - 0.0595 \log IO3'$  at 25°. The solubility of Cu(IO3)2 in H2O is  $3.30 + 10^{-3}$  mols per liter at 25°. Both KIO3 and CuSO4 reduce the solubility normally and do not produce any soluble complex salt. In a saturated aqueous solution of

Cu(IO3)2, the

concentrate of Cu++ is  $7.88 + 10^{-3}$  instead of  $3.30 + 10^{-3}$  which it should be if the compound were completely ionized; that of IO3- is  $4.31 + 10^{-3}$  instead of  $6.60 + 10^{-3}$ , indicating that the solid Cu(IO3)2 takes up IO3- probably by the formation of a complex mol. which is unstable in solution

CC 6 (Inorganic Chemistry)

IT 13454-89-2, Copper iodate  
(preparation of)IT 13454-89-2, Copper iodate  
(preparation of)

=&gt; d L18 1 all

YOU HAVE REQUESTED DATA FROM FILE 'WPIX' - CONTINUE? (Y)/N:n

=&gt; file wpix

FILE 'WPIX' ENTERED AT 11:24:33 ON 03 DEC 2003

COPYRIGHT (C) 2003 THOMSON DERWENT

FILE LAST UPDATED: 28 NOV 2003 &lt;20031128/UP&gt;

MOST RECENT DERWENT UPDATE: 200377 &lt;200377/DW&gt;

DERWENT WORLD PATENTS INDEX SUBSCRIBER FILE, COVERS 1963 TO DATE

=&gt; d L18 1 all

L18 ANSWER 1 OF 1 WPIX COPYRIGHT 2003 THOMSON DERWENT on STN

AN 2003-521797 [49] WPIX  
DNN N2003-413946 DNC C2003-140230  
TI **Electrochemical cell** comprises anode containing anode active material, aqueous alkaline electrolyte solution, separator and cathode containing **copper iodate**.  
DC E36 L03 X16  
IN ANGLIN, D; DRENNAN, J; ROZELLE, J; WANG, E I; WANG, F P; XUE, J S  
PA (ANGL-I) ANGLIN D; (DREN-I) DRENNAN J; (ROZE-I) ROZELLE J; (WANG-I) WANG E I; (WANG-I) WANG F P; (XUEJ-I) XUE J S  
CYC 1  
PI US 2003049530 A1 20030313 (200349)\* 11p H01M004-48  
ADT US 2003049530 A1 US 2001-941526 20010829  
PRAI US 2001-941526 20010829  
IC ICM H01M004-48  
ICS H01M004-58; H01M004-62  
AB US2003049530 A UPAB: 20030731  
NOVELTY - An **electrochemical cell** (810) comprises an anode (815) containing an anode active material, an aqueous alkaline electrolyte solution, a separator and a cathode (812) containing **copper iodate**.  
USE - **Electrochemical cell**.  
ADVANTAGE - The **electrochemical cell** has improved electrical conductivity using graphitic carbon and improved cell performance using sulfur and **copper iodate**. The running voltage of the cell is reduced and hence increased power and cell life are obtained.  
DESCRIPTION OF DRAWING(S) - The figure shows a cross-sectional portion of the alkaline cell.  
cell 810  
cathode 812  
anode 815  
Dwg.1/2  
FS CPI EPI  
FA AB; GI; DCN  
MC CPI: E11-N; E33-A03; E35-C; L03-E01A; L03-E01B8; L03-E01C2  
EPI: X16-B01A; X16-E01C; X16-E01E; X16-E09; X16-J02; X16-J07

=&gt;